

Domain-dependent Text Structures

Regina Barzilay

March 1, 2003

What is Text?

A product of cohesive ties (cohesion)

ATHENS, Greece (Ap) A strong earthquake shook the Aegean Sea island of Crete on Sunday but caused no injuries or damage. The quake had a preliminary magnitude of 5.2 and occurred at 5:28 am (0328 GMT) on the sea floor 70 kilometers (44 miles) south of the Cretan port of Chania. The Athens seismological institute said the temblor's epicenter was located 380 kilometers (238 miles) south of the capital. No injuries or damage were reported.

What is Text?

A product of structural relations (coherence)

S_1 : A strong earthquake shook the Aegean Sea island of Crete on Sunday


S_2 : but caused no injuries or damage.

S_3 : The quake had a preliminary magnitude of 5.2

Content-based Structure

- Describe the strength and the impact of an earthquake
- Specify its magnitude
- Specify its location
- ...

Rhetorical Structure



Analogy with Syntax

Domain-independent Theory of Sentence Structure

- Fixed set of word categories (nouns, verbs, ...)
- Fixed set of relations (subject, object, ...)

P("A is sentence this weird")

Two Approaches to Text Structure

- Domain-dependent models (Today)
 - Content-based models
 - Rhetorical models
- Domain-independent models
 - Rhetorical Structure Theory (Next Class)

Motivation

- Summarization
Extract a representative subsequence from a set of sentences
- Question-Answering
Find an answer to a question in natural language
- Text Ordering
Order a set of information-bearing items into a coherent text
- Machine Translation
Find the best translation taking context into account

Today: Domain-Specific Models

- Rhetorical Models:
 - Argumentative Zoning of Scientific Articles (Teufel, 1999)
- Content-based Models:
 - Supervised (Duboue&McKeown, 2001)
 - Unsupervised (Barzilay&Lee, 2004)

Argumentative Zoning

Many of the recent advances in Question Answering have followed from the insight that systems can benefit from by exploiting the redundancy in large corpora.

Brill et al. (2001) describe using the vast amount of data available on the WWW to achieve impressive performance ...

The Web, while nearly infinite in content, is not a complete repository of useful information ...

In order to combat these inadequacies, we propose a strategy in which information is extracted from ...

Argumentative Zoning

BACKGROUND

Many of the recent advances in Question Answering have followed from the insight that systems can benefit from by exploiting the redundancy . . .

OTHER WORK

Brill et al. (2001) describe using the vast amount of data available on the WWW to achieve impressive performance . . .

WEAKNESS

The Web, while nearly infinite in content, is not a complete repository of useful information . . .

OWN CONTRIBUTION

In order to combat these inadequacies, we propose a strategy in which information is extracted from . . .

Motivation

- Scientific articles exhibit (consistent across domains) similarity in structure
 - BACKGROUND
 - OWN CONTRIBUTION
 - RELATION TO OTHER WORK
- Automatic structure analysis can benefit:
 - Q&A
 - summarization
 - citation analysis

Approach

- Goal: Rhetorical segmentation with labeling
- Annotation Scheme:
 - Own work: aim, own, textual
 - Background
 - Other Work: contrast, basis, other
- Implementation: Classification

Examples

Category	Realization
Aim	We have proposed a method of clustering words based on large corpus data
Textual	Section 2 describes three parsers which are ...
Contrast	However, no method for extracting the relationship from superficial linguistic expressions was described in their paper.

Kappa Statistics

(Siegal&Castellan, 1998; Carletta, 1999)

Kappa controls agreement $P(A)$ for chance agreement $P(E)$

$$K = \frac{P(A) - p(E)}{1 - p(E)}$$

Kappa from Argumentative Zoning:

- Stability: 0.83
- Reproducibility: 0.79

Features

- Position
- Verb Tense and Voice
- History
- Lexical Features (“other researchers claim that”)

Results

- Classification accuracy is above 70%
- Zoning improves classification

Supervised Content Modeling

(Duboue& McKeown, 2001)

- Goal: Find types of semantic information characteristic to a domain and ordering constraints on their presentation
- Approach: find patterns in a set of transcripts manually annotated with semantic units
- Domain: Patients records

Annotated Transcript

He is 58-year-old male. History is significant for Hodgkin's disease,
age gender pmh
treated with ...to his neck, back and chest. Hyperspadias, BPH,
pmh pmh
hiatal hernia and proliferative lymph edema in his right arm. No IV's
pmh pmh
or blood pressure down in the left arm. Medications — Inderal, Lopid,
med-preop med-preop
Pepcid, nitroglycerine and heparin. EKG has PAC's. ...
med-preop drip-preop med-preop ekg-preop

Semantic Sequence

age, gender, pmh, pmh, pmh, pmh, med-preop,
med-preop, med-preop, drip-preop, med-preop,
ekg-preop, echo-preop, hct-preop, procedure, ...

Pattern Detection

Analogous to motif detection

T_1 : A B C D F A A B F D

T_2 : F C A B D D F F

- Scanning
- Generalizing
- Filtering

Example of Learned Pattern

intraop-problems

intraop-problems

{	operation	11.11%	}
	drip	33.33%	
	intraop-problems	33.33%	
	total-meds-anesthetics	22.22%	

drip

Evaluation

Pattern confidence: 84.62%

Constraint accuracy: 89.45%

Content Models

(Barzilay&Lee, 2004)

- Content models represent topics and their ordering in text.

Domain: newspaper articles on earthquake

Topics: “strength”, “location”, “casualties”, ...

Order: “casualties” prior to “rescue efforts”

- Assumption: Patterns in content organization are recurrent

Similarity in Domain Texts

TOKYO (AP) A moderately strong earthquake with a preliminary magnitude reading of 5.1 rattled northern Japan early Wednesday, the Central Meteorological Agency said. There were no immediate reports of casualties or damage. The quake struck at 6:06 am (2106 GMT) 60 kilometers (36 miles) beneath the Pacific Ocean near the northern tip of the main island of Honshu. ...

ATHENS, Greece (AP) A strong earthquake shook the Aegean Sea island of Crete on Sunday but caused no injuries or damage. The quake had a preliminary magnitude of 5.2 and occurred at 5:28 am (0328 GMT) on the sea floor 70 kilometers (44 miles) south of the Cretan port of Chania. The Athens seismological institute said the temblor's epicenter was located 380 kilometers (238 miles) south of the capital. No injuries or damage were reported.

Similarity in Domain Texts

TOKYO (AP) A moderately strong earthquake with a preliminary magnitude reading of 5.1 rattled northern Japan early Wednesday, the Central Meteorological Agency said. There were no immediate reports of casualties or damage. The quake struck at 6:06 am (2106 GMT) 60 kilometers (36 miles) beneath the Pacific Ocean near the northern tip of the main island of Honshu. ...

ATHENS, Greece (Ap) A strong earthquake shook the Aegean Sea island of Crete on Sunday but caused no injuries or damage. The quake had a preliminary magnitude of 5.2 and occurred at 5:28 am (0328 GMT) on the sea floor 70 kilometers (44 miles) south of the Cretan port of Chania. The Athens seismological institute said the temblor's epicenter was located 380 kilometers (238 miles) south of the capital. ...


Narrative Grammars

- Propp (1928): fairy tales follow a “story grammar”
- Barlett (1932): formulaic text structure facilitates reader’s comprehension
- Wray (2002): texts in multiple domains exhibit significant structural similarity

Computing Content Model

Implementation: Hidden Markov Model

- States represent topics
- State-transitions represent ordering constraints



Model Construction

- Initial topic induction
- Determining states, emission and transition probabilities
- Viterbi re-estimation

Initial Topic Induction

Agglomerative clustering with cosine similarity measure

(Iyer&Ostendorf:1996,Florian&Yarowsky:1999, Barzilay&Elhadad:2003)


The Athens seismological institute said the temblor's epicenter was located 380 kilometers (238 miles) south of the capital.

Seismologists in Pakistan's Northwest Frontier Province said the temblor's epicenter was about 250 kilometers (155 miles) north of the provincial capital Peshawar.

The temblor was centered 60 kilometers (35 miles) northwest of the provincial capital of Kunming, about 2,200 kilometers (1,300 miles) southwest of Beijing, a bureau seismologist said.

From Clusters to States

- Each large cluster constitutes a state
- Agglomerate small clusters into an “*insert*” state



Estimating Emission Probabilities

State s_i emission probability:

$$p_{s_i}(w_0, \dots, w_n) = \prod_{j=0}^n p_{s_i}(w_j | w_{j-1})$$


- Estimation for a “normal” state:

$$p_{s_i}(w' | w) \stackrel{\text{def}}{=} \frac{f_{c_i}(ww') + \delta_1}{f_{c_i}(w) + \delta_1 |V|},$$

- Estimation for the “insertion” state:

$$p_{s_m}(w' | w) \stackrel{\text{def}}{=} \frac{1 - \max_{i < m} p_{s_i}(w' | w)}{\sum_{u \in V} (1 - \max_{i < m} p_{s_i}(u | w))}.$$

Estimating Transition Probabilities



$$p(s_j | s_i) = \frac{g(c_i, c_j) + \delta_2}{g(c_i) + \delta_2 m}$$


$g(c_i, c_j)$ is a number of adjacent sentences (c_i, c_j)

$g(c_i)$ is a number of sentences in c_i

Viterbi re-estimation

Goal: incorporate ordering information

- Decode the training data with Viterbi decoding



- Use the new clustering as the input to the parameter estimation procedure

Application: Information Ordering

- Input: set of sentences
- Applications:
 - Text summarization
 - Natural Language Generation
- Goal: Recover most likely sequences
“*get marry*” prior to “*give birth*” (in some domains)

Information Ordering: Algorithm

Input: set of sentences

- Produce all permutations of the set
- Rank them based on the content model

Application: Summarization

- Domain-dependent summarization: (Radev&McKeown:1998)
 - specify types of important information (manually)
 - use information extraction to identify this information (automatically)
- Domain-independent summarization: (Kupiec et al:1995)
 - represent a sentence using shallow features
 - use a classifier

Summarization: Algorithm

Input: source text

Training data: parallel corpus of summaries and source texts (aligned)

- Employ Viterbi on source texts and summaries
- Compute state likelihood to generate summary sentences:

$$p(s \in \text{summary} | s \in \text{source}) = \frac{\text{summary_count}(s)}{\text{source_count}(s)},$$

- Given a new text, decode it and extract sentences corresponding to “summary” states

Evaluation: Data

Domain	Average Length	Vocabulary Size	Token/type
Earthquake	10.4	1182	13.158
Clashes	14	1302	4.464
Drugs	10.3	1566	4.098
Finance	13.7	1378	12.821
Accidents	11.5	2003	5.556

Baselines for Ordering

- “Straw” baseline: Bigram Language model
- “State-of-the-art” baseline: (Lapata:2003)
 - represent a sentence using lexico-syntactic features
 - compute pairwise ordering preferences
 - find optimally global order


Results: Ordering

Domain	Algorithm	Prediction Accuracy	Rank	τ
Earthquake	Content	72%	2.67	0.81
	Lapata '03	24%	(N/A)	0.48
	Bigram	4%	485.16	0.27
Clashes	Content	48%	3.05	0.64
	Lapata '03	27%	(N/A)	0.41
	Bigram	12%	635.15	0.25
Drugs	Content	38%	15.38	0.45
	Lapata '03	27%	(N/A)	0.49
	Bigram	11%	712.03	0.24
Finance	Content	96%	0.05	0.98
	Lapata '03	17%	(N/A)	0.44
	Bigram	66%	7.44	0.74
Accidents	Content	41%	10.96	0.44
	Lapata '03	10%	(N/A)	0.07
	Bigram	2%	973.75	0.19

Baselines for Summarization

- “Straw” baseline: n leading sentences
- “State-of-the-art” Kupiec-style classifier:
 - Sentence representation: lexical features and location
 - Classifier: BoosTexter

Ordering: Learning Curve



Results: Summarization

Summarizer	Extraction accuracy
Content-based	88%
Sentence classifier (words + location)	76%
Leading n sentences	69%

Summarization: Learning Curve

